

# Interface® Hospitality

## Havana Nights

	GlasBac® Tile
PRODUCT NUMBER:	1286002500
PRODUCT CONSTRUCTION:	Tufted Sheared
STANDARD COLORLINE:	1
YARN SYSTEM:	100% Recycled Content Type 6 Nylon
YARN MANUFACTURER:	Aquafil
DYE METHOD:	100% Solution Dyed
RECYCLED CONTENT:	
Post Industrial Range:	32% - 32%
Post Consumer:	13%
Total Recycled Content:	45% - 45%
SOIL/STAIN PROTECTION:	Protekt <sup>2</sup> ®
ANTIMICROBIAL:	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

PRODUCT SPECIFICATIONS	U.S.	METRIC
TUFTED YARN WEIGHT:	34 oz/yd <sup>2</sup>	1153.0 g/m <sup>2</sup>
MACHINE GAUGE:	1/10 in	39.4 ends/10 cm
PILE HEIGHT:	0.19 in	4.8 mm
PILE THICKNESS:	0.131 in	3.3 mm
STITCHES:	10.00 /in	39.37 ends/10 cm
PILE DENSITY:	9344	
TRAFFIC CLASSIFICATION:	Heavy	
FIBER MODIFICATION RATIO:	1.9 to 2.2	
SIZE:	19.69 in x 19.69 in	50 cm x 50 cm

## PERFORMANCE SPECIFICATIONS

Radiant Panel:	(ASTM E-648) Class 1
Smoke Density:	(ASTM E - 662) ≤450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static:	(AATCC - 134) < 3.0 KV
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing:	GlasBac® Tile
Backing Options:	GlasBac® Tile, GlasBac® RE Tile, NexStep® Tile

## INSTALLATION

Tile:	Ashlar, Brick, Monolithic
-------	---------------------------

All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. "Tufted Yarn Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting and shearing will result in a lower finished yarn weight in purchased carpet. Pile Density stated in the Product Specifications is based on the Tufted Yarn Weight. Product Specifications may be changed without notice as long as product performance is not materially affected.

# Interface® Hospitality

## Havana Nights

	GlasBac RE® Tile
PRODUCT NUMBER:	128600250H
PRODUCT CONSTRUCTION:	Tufted Sheared
STANDARD COLORLINE:	1
YARN SYSTEM:	100% Recycled Content Type 6 Nylon
YARN MANUFACTURER:	Aquafil
DYE METHOD:	100% Solution Dyed
RECYCLED CONTENT:	
Post Industrial Range:	45% - 45%
Post Consumer:	36%
Total Recycled Content:	81% - 81%
SOIL/STAIN PROTECTION:	Protekt <sup>2</sup> ®
ANTIMICROBIAL:	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

PRODUCT SPECIFICATIONS	U.S.	METRIC
TUFTED YARN WEIGHT:	34 oz/yd <sup>2</sup>	1153.0 g/m <sup>2</sup>
MACHINE GAUGE:	1/10 in	39.4 ends/10 cm
PILE HEIGHT:	0.19 in	4.8 mm
PILE THICKNESS:	0.131 in	3.3 mm
STITCHES:	10.00 /in	39.37 ends/10 cm
PILE DENSITY:	9344	
TRAFFIC CLASSIFICATION:	Heavy	
FIBER MODIFICATION RATIO:	1.9 to 2.2	
SIZE:	19.69 in x 19.69 in	50 cm x 50 cm

## PERFORMANCE SPECIFICATIONS

Radiant Panel:	(ASTM E-648) Class 1
Smoke Density:	(ASTM E - 662) ≤450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static:	(AATCC - 134) < 3.0 KV
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing:	GlasBac® Tile
Backing Options:	GlasBac® Tile, GlasBac® RE Tile, NexStep® Tile

## INSTALLATION

Tile:	Ashlar, Brick, Monolithic
-------	---------------------------

All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. "Tufted Yarn Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting and shearing will result in a lower finished yarn weight in purchased carpet. Pile Density stated in the Product Specifications is based on the Tufted Yarn Weight. Product Specifications may be changed without notice as long as product performance is not materially affected.

# Interface® Hospitality

## Havana Nights

	NexStep® Tile
PRODUCT NUMBER:	128600250M
PRODUCT CONSTRUCTION:	Tufted Sheared
STANDARD COLORLINE:	1
YARN SYSTEM:	100% Recycled Content Type 6 Nylon
YARN MANUFACTURER:	Aquafil
DYE METHOD:	100% Solution Dyed
RECYCLED CONTENT:	
Post Industrial Range:	27% - 27%
Post Consumer:	18%
Total Recycled Content:	45% - 45%
SOIL/STAIN PROTECTION:	Protekt <sup>2</sup> ®
ANTIMICROBIAL:	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

PRODUCT SPECIFICATIONS	U.S.	METRIC
TUFTED YARN WEIGHT:	34 oz/yd <sup>2</sup>	1153.0 g/m <sup>2</sup>
MACHINE GAUGE:	1/10 in	39.4 ends/10 cm
PILE HEIGHT:	0.19 in	4.8 mm
PILE THICKNESS:	0.131 in	3.3 mm
STITCHES:	10.00 /in	39.37 ends/10 cm
PILE DENSITY:	9344	
TRAFFIC CLASSIFICATION:	Heavy	
FIBER MODIFICATION RATIO:	1.9 to 2.2	
SIZE:	19.69 in x 19.69 in	50 cm x 50 cm

## PERFORMANCE SPECIFICATIONS

Radiant Panel:	(ASTM E-648) Class 1
Smoke Density:	(ASTM E - 662) ≤450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static:	(AATCC - 134) < 3.0 KV
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing:	GlasBac® Tile
Backing Options:	GlasBac® Tile, GlasBac® RE Tile, NexStep® Tile

## INSTALLATION

Tile:	Ashlar, Brick, Monolithic
-------	---------------------------

All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. "Tufted Yarn Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting and shearing will result in a lower finished yarn weight in purchased carpet. Pile Density stated in the Product Specifications is based on the Tufted Yarn Weight. Product Specifications may be changed without notice as long as product performance is not materially affected.